




# DIN 963

strona 2

EN 22009  
ISO 2009  
PN 82207



Wkręt do metalu z łbem stożkowym,  
z nacięciem prostym

A2 / A4

dk	14,5	18,0	22,0	25,0	29,0	33,0	36,0
k	4,0	5,0	6,0	7,0	8,0	9,0	10,0

d	M 8	M 10	M 12	M 14	M 16	M 18	M 20
---	-----	------	------	------	------	------	------

l	10	12	14	16	18	20	22	25	28	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	110	120	130	140	150	160	
M 8	200	200	200	200	200	200	200	200	200	200	200	200	200	200	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	
M 10				100						100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	
M 12						50				50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	
M 14							25			25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	
M 16								25		25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	
M 18																25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	
M 20																									25	25	25	25	25	25	25

Ilość szt. w opakowaniu jednostkowym