



DIN 7983 PH

EN 27051
ISO 7051
PN 83115

Blachowkręt z łbem soczewkowym,
z gniazdem krzyżowym PH

A2 / A4



| dk | 4,3 | 5,5 | 6,8 | 7,5 | 8,1 | 9,5 | 10,8 | 12,4 |
|---------|-----|-----|-----|-----|-----|-----|------|------|
| k | 1,3 | 1,7 | 2,1 | 2,3 | 2,5 | 3,0 | 3,4 | 3,8 |
| t | 2,8 | 3,4 | 4,6 | 4,7 | 4,9 | 5,4 | 7,0 | 7,4 |
| f | 0,7 | 0,9 | 1,2 | 1,3 | 1,4 | 1,5 | 1,7 | 2,0 |
| gniazdo | PH1 | PH1 | PH2 | PH2 | PH2 | PH2 | PH3 | PH3 |

| d | 2,2 | 2,9 | 3,5 | 3,9 | 4,2 | 4,8 | 5,5 | 6,3 |
|---|-----|-----|-----|-----|-----|-----|-----|-----|
|---|-----|-----|-----|-----|-----|-----|-----|-----|

| l | 6,5 | 9,5 | 13,0 | 16,0 | 19,0 | 22,0 | 25,0 | 32,0 | 38,0 | 45,0 | 50,0 | 60,0 | 70,0 | 80,0 | 90,0 | 100,0 | 110,0 | 120,0 |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|
| 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 |
| 500 | | | | | | | | | | | | | | | | | | 500 |
| 200 | | | | | | | | | | | | | | | | | | 200 |
| 100 | | | | | | | | | | | | | | | | | | 100 |
| 50 | | | | | | | | | | | | | | | | | | 50 |
| 20 | | | | | | | | | | | | | | | | | | 20 |
| 10 | | | | | | | | | | | | | | | | | | 10 |
| 5 | | | | | | | | | | | | | | | | | | 5 |
| 2 | | | | | | | | | | | | | | | | | | 2 |
| 1 | | | | | | | | | | | | | | | | | | 1 |

Ilość szt. w opakowaniu jednostkowym