



DIN 439

EN 24035
 ISO 4035
 PN 82153

Nakrętka sześciokątna niska
 A2 / A4



d	m	e	s	
M 1,6	1,0	3,48	3,2	1000
M 1,7	1,1	3,48	3,2	500
M 2	1,2	4,32	4,0	1000
M 2,3	1,2	5,20	4,5	1000
M 2,5	1,6	5,45	5,0	1000
M 2,6	1,6	5,80	5,0	1000
M 3	1,8	6,01	5,5	1000
M 4	2,2	7,86	7,0	1000
M 5	2,7	8,79	8,0	1000
M 6	3,2	11,05	10,0	1000
M 8	4,0	14,38	13,0	500
M 10	5,0	18,90	17,0	200
M 12	6,0	21,10	19,0	200
M 14	7,0	24,49	22,0	100
M 16	8,0	26,75	24,0	100
M 18	9,0	29,65	27,0	50
M 20	10,0	32,95	30,0	50
M 22	11,0	35,03	32,0	25
M 24	12,0	39,55	36,0	25
M 27	13,5	45,20	41,0	25
M 30	15,0	50,85	46,0	25
M 33	16,5	55,37	50,0	10
M 36	18,0	60,79	55,0	10
M 39	19,5	66,40	60,0	10
M 42	21,0	71,30	65,0	10
M 45	22,5	76,95	70,0	10
M 48	24,0	82,60	75,0	10